



Manufacturing Intelligent Compressed Air Products Since 1983

11510 Goldcoast Drive, Cincinnati, OH, USA 45249-1621

(513) 671-3322 FAX (513) 671-3363 Email: techhelp@exair.com



LIT6903

Air Wipe Shim Set

The aluminum Standard Air Wipe has a .002" (.05mm) thick (red) shim installed. Plastic Shim Sets include (1) .001" (.03mm) thick shim (amber), (1) .003" (.08mm) thick shim (green) and (1) .004" (.10mm) thick shim (tan).

The aluminum Super Air Wipe and the stainless steel Super Air Wipe have a .002" (0.5mm) thick stainless steel shim installed. Stainless steel Shim Sets for the Super Air Wipe include (2) .002" (.05mm) thick stainless steel shims. Shims may be interchanged or stacked to change the air gap setting. The shim thickness sets the air gap opening. Larger air gaps give more flow and higher velocity. Air consumption doubles if the air gap opening doubles.

If you have any questions or problems, please contact an EXAIR Application Engineer at:

Toll Free: 1-800-903-9247 (US & Canada)
Toll Free Fax: 866-329-3924 (US & Canada)
E-mail: techhelp@exair.com

Telephone: 513 671-3322 outside of US & Canada
Fax: 513 671-3363 outside of US & Canada
Website: www.exair.com