


XAFF

Pressure-fed/Int. Mix/Deflected Flat Fan

DESIGN/SPRAY CHARACTERISTICS

- Internal mix
- Deflected flat fan spray pattern



1/4"XA 01 FF050 F
XA01 Body; F Hardware

XA FF Set-up Flow Rates

Pressure-fed, Internal Mix, Deflected Flat Fan Spray Pattern, 1/8" and 1/4" Pipe Sizes


Pipe Size	Spray Set-up Number	Fluid and Air Cap Numbers	10 PSI Liquid			20 PSI Liquid			30 PSI Liquid			40 PSI Liquid			60 PSI Liquid		
			PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM
1/8 or 1/4	FF 050	Fluid Cap FC10 & Air Cap AC1701	6	2.9	1.6	14	3.9	2.6	22	4.7	3.3	26	5.8	3.6	38	7.4	4.6
			8	2.5	1.9	16	3.5	2.8	24	4.3	3.6	32	4.8	4.4	46	6.4	5.5
			10	2.0	2.3	18	3.1	3.1	26	4.0	3.8	38	3.8	5.3	54	5.3	6.6
			12	1.5	2.7	20	2.8	3.5	30	3.3	4.5	44	2.8	6.2	62	4.2	7.8
			22	2.3	3.8	34	2.3	5.2	46	2.3	6.6	70	2.8	9.4			

XAXW

Pressure-fed/Int. Mix/Extra-wide Angle

DESIGN/SPRAY CHARACTERISTICS

- Internal mix
- 180° Extra-wide hollow cone



1/4"XA 03 XW050 A
XA 03 Body; A Hardware

XA XW Set-up Flow Rates

Pressure-fed, Internal Mix, Extra-Wide Spray pattern, 1/8" and 1/4" Pipe Sizes

Pipe Size	Spray Set-up Number	Fluid and Air Cap Numbers	10 PSI Liquid			20 PSI Liquid			30 PSI Liquid			40 PSI Liquid			60 PSI Liquid		
			PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM	PSI air	GPH	SCFM
1/8 or 1/4	XW 050	Fluid Cap FC8 & Air Cap AC1401	20	4.0	2.5	34	6.6	4.1	50	7.1	6.4	60	11.0	7.6	85	14.4	11.8
			22	2.8	2.7	38	4.4	4.8	52	6.2	6.8	65	8.3	8.6	90	12.0	13.0
			24	2.0	3.0	42	2.8	5.5	56	4.4	7.6	70	6.1	9.8	95	9.8	14.1
			26	1.5	3.3	46	1.7	6.3	60	3.2	8.4	80	3.1	12.4	100	7.8	15.4
			28	1.1	3.6	48	1.3	6.9	70	1.3	11.8	90	1.4	15.4			

Standard Materials: Nickel Plated Brass, 303 Stainless Steel and 316 Stainless Steel.

AIR ATOMIZING

CALL 413-772-0846
Call for the name of your nearest BETE representative.